














DESCRIPTION	TEST	RESULT	
<b>PHYSICAL CHARACTERISTICS</b>			
	Dimensions and surface quality	ISO 10545-2	Guaranteed
	Water absorption	ISO 10545-3	3,0%<E≤6,0%
	Modulus of rupture	ISO 10545-4	Guaranteed
	Resistance to flexion	ISO 10545-4	Guaranteed
	Impact resistance	ISO 10545-5	Guaranteed Not damage appreciated in tested pieces
	Resistance to deep abrasion	ISO 10545-6	Guaranteed
	Frost resistance	ISO 10545-12	Guaranteed
	Resistance to thermal shock	ISO 10545-9	Guaranteed
<b>SLIP RESISTANCE</b>			
	Slip resistance	UNE-ENV 12633:2003 Anexo A	Class 3 (maximun)
	Static friction coefficient	ASTM 1028-96	Guaranteed
	Dinamic friction coefficient	ISO/DIS 10545-17	Guaranteed
<b>CHEMICAL CHARACTERISTICS</b>			
	Chemical resistance	UNE-EN ISO 10545-13	Guaranteed Not damage appreciated in tested pieces
	Cleaning products and pools additives	UNE-EN ISO 10545-13	Guaranteed Not damage appreciated in tested pieces